ZITHA TECH SPECIALTY CABLES (Pty) Ltd

Belarusian Tunable Optical Module QSFP-DD



Overview

Full C-band tunable, 75GHz or 100GHz grid Case temperature range 0°C to 70°C Power dissipation < 18. 5W implementation agreement The FS QSFP-DD Digital Coherent Optics (DCO) transceiver supports 400G coherent transmission for data center interconnect and metro/edge. Cisco QSFP-DD and OSFP 800G ZR/ZR+ digital coherent optics modules enable 800G traffic over amplified Dense Wavelength-Division Multiplexing (DWDM) links up to 120 km for 800ZR and over 1000 km for 800G ZR+. The module is based. Quad Small Form-factor Pluggable Double Density (QSFP-DD) solution that fits into high-density switch and router client ports for optical interconnect links Powered by Greylock and Delphi DSP ASICs, and silicon photonic integrated circuits (PICs) for an optimized co-packaged design with 3D. ZR+, Standard Tx output power (-10dBm), C-band tunable, Pull tab, 0°C to 70°C, LC receptacle The emerging OIF 400ZR and Open ZR+ MSA coherent transceivers in QSFP-DD and OSFP form factors generally have low transmit output power (-10 dBm), making them incompatible with ROADM networks. Consequently. Smartoptics QSFP-DD transceivers provide cost-efficient 400G and 800G optical networking. QSFP-DD (Quad Small Form-Factor Pluggable Double Density) transceivers double the number of high-speed electrical interfaces in QSFP to achieve 400G Ethernet speeds – and double them again to reach 800G. As a. This article provides a comprehensive comparison of mainstream optical transceivers, including SFP, SFP+, QSFP+, QSFP28, and QSFP-DD. It explains their technical differences, compatibility considerations, and ideal use cases to help readers choose the right module for enterprise and data center.

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

Article Content

Cisco QSFP-DD and OSFP 800G ZR/ZR+ Coherent Optics Modules

They expand Cisco routed optical networking applications to include 800G links and are compatible with Cisco and third-party 800G-capable routers, switches, and transponders with QSFP

QSFP-DD Product Family » Acacia

Powered by Greylock and Delphi DSP ASICs, and silicon photonic integrated circuits (PICs) for an optimized co-packaged design with 3D Siliconization. Supports an expansive list of interoperability

Optical Transceiver: SFP vs SFP+ vs QSFP28 vs QSFP-DD

This article provides a comprehensive comparison of mainstream optical transceivers, including SFP, SFP+, QSFP+, QSFP28, and QSFP-DD. It explains their technical differences,

QSFP-DD DCO 400G DWDM Tunable Coherent ≤120km DOM

Using C-FEC and 16QAM modulation, the module supports 400G tunable WDM transmission per wavelength, with up to 40km unamplified and 120km amplified reach. It is intended to be used in

100G QSFP-DD DCO : Optical Transceiver Module | NEC

The NEC''s 100G QSFP-DD DCO optical transceiver is an optical transceiver that utilizes coherent technology. QSFP-DD has backward compatibility with existing form factors such as QSFP+ and

QSFP-DD 100G DWDM Coh Tunable SM 450km, CMIS5.0 LC

The TQD011-TUNC-SO is an QSFP-DD form-factor (type 2a) DWDM transceiver for coherent 100Gbps Ethernet applications. The transceiver is intended for use in interconnect applications between data

QSFP-DD DCO Optical Transceiver Modules | AscentOptics

The product family supports 100/400Gbps transmission speeds in an industry-standard, pluggable QSFP-DD form factor with DSP and can be widely used in metro carrier, access, and Cloud/DCI

QSFPDD-ZR-400G Datasheet | FS

400G QSFP-DD DCO DWDM TUNABLE COHERENT 120KM DOM TRANSCEVER Description The FS QSFP-DD Digital Coherent Optics (DCO) transceiver supports 400G coherent transmission for data

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

100G QSFP-DD ZR+ Coherent, Tunable, 1000km,

The MJ-QSDD-100G-ZR+ is a QSFP-DD type transceiver, which works with tunable channels and uses 16AQM modulation to provide 100Gb/s of coherent optical

400GBASE ZR QSFP-DD DWDM LC SMF SiPh Optical Transceiver Module

The 400G QSFP-DD ZR is designed to 400G 120Km DCI DWDM applications without inline chromatic dispersion compensation.
The 400G QSFP-DD ZR is a C-Band optical frequency tunable

Contact Us

Continue your research online:

Website: https://zithatech.co.za
Technical inquiry: https://zithatech.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved